

Part No: MCT705xxS-AW Series

1.5mm² Stranded PACW, V-90 PVC insulated, Tripled, cabled, overall Description aluminium laminate screened with a 7/0.20mm TAC drain wire, 5V-90

PVC overall jacketed, instrumentation and ELV control cable.

Applicable Standards AS/NZS 1125, AS/NZS 3808, IEC 60332-1

Instrument and control cable for use in industrial applications including

the interconnection of signals between cabinets, consoles, sensors and display panels


display panels.

Not Suitable for mains connection.

Cable Construction Drawing

Cable Construction Relative Parts







3 triad cable shown for illustration purposes. Other pair counts of similar construction Refer to Construction table

Cable Construction

Conductor	Standard	AS/NZS 1125 or IEC 60228		
	Conductor class	Class 2 – Stranded conductor		
	Material	PACW		
	Nom. Stranding	7/0.5 mm		

With Garland, you are always well connected.





Insulation	Material	V-90 PVC		
		Wire 1: Black		
		Wire 2: White		
	Colours:	Wire 3: Red		
		For cables with 2 or more triads the insulation is numbered with the triad number		
Insulation	Nom Diameter:	2.3 mm		
	Nom Thickness:	0.4 mm		
Basic Element	Twins	Black & White conductors twinned together		
Overall Taping and Screening	Material	Polyester or PET tape		
	Drain wire	7/0.2mm (nominal) TAC drain wire		
	Overall screen	Aluminium/Polyester laminate. Aluminium facing in and in contact with the drain wire		
	Coverage	100%		
Sheath	Material:	5V-90 PVC		
	Colour:	Black		
	Nominal Diameter:	Refer to construction table		
	Nominal Thickness:	Refer to construction table		

110VAC, 150VDC	
≤ 13.6 Ohms/km @ 20°C	
<250 pF/m	
≤0.95 µH/m	
35 μΗ/Ω	
	≤ 13.6 Ohms/km @ 20°C <250 pF/m ≤0.95 μH/m

Mechanical Properties	
Operating Temperature Range	-15 to 90℃
Min. Bend Radius (install)	18 x Diameter

With Garland, you are always well connected.





Construction Table								
Part Number	Nos of Triads	Pack size ¹ (m)	Screen	Jacket Colour ²	Nom. Cable Diameter (mm)	Nom Jacket Thickness (mm)	Approx Weight (Kg/Km)	
MCT7051S100-AW	1	100	Overall	Black	6.8	0.7	75	
MCT7051S500-AW	1	500	Overall	Black	6.8	0.7	75	
MCT7051S1000-AW	1	1000	Overall	Black	6.8	0.7	75	
MCT7052S100-AW	2	100	Overall	Black	11.2	1.0	155	
MCT7052S500-AW	2	500	Overall	Black	11.2	1.0	155	
MCT7052S1000-AW	2	1000	Overall	Black	11.2	1.0	155	
MCT7053S100-AW	3	100	Overall	Black	12.1	1.1	213	
MCT7053S500-AW	3	500	Overall	Black	12.1	1.1	213	
MCT7053S1000-AW	3	1000	Overall	Black	12.1	1.1	213	
MCT7054S100-AW	4	100	Overall	Black	13.3	1.1	269	
MCT7054S500-AW	4	500	Overall	Black	13.3	1.1	269	
MCT7054S1000-AW	4	1000	Overall	Black	13.3	1.1	269	
MCT7056S500-AW	6	500	Overall	Black	16.3	1.3	398	
MCT7056S1000-AW	6	1000	Overall	Black	16.3	1.3	398	
MCT7058S500-AW	8	500	Overall	Black	18.0	1.5	522	
MCT7058S1000-AW	8	1000	Overall	Black	18.0	1.5	522	

- Madison reserves the right to make changes to the products described in this specification without prior notice
- All values subject to factory tolerances



With Garland, you are always well connected.

 $^{^{\}mathrm{1}}$ Other lengths available subject to negotiation. MoQ and lead time restrictions may apply

² Other colours available upon request. MoQ and lead time restrictions may apply