Server Rack 42U



Part No:	GDR42U600X800FMD
----------	------------------

Data Racks / Floor Racks

Description	42U 600x800 Floor Rack with mesh front, and rear mesh split lockable Doors. Removable and lockable side panels, top panel with ventilation holes and four cable entry points, bottom panel with two cable entry points. 4 Fan tray with thermostat, 3 fixed shelf, 8 way PDU with overload protection and switch, adjustable rails, levelling feet with heavy duty castors, grounding lugs, 40 x Nut/Bolt/washers, 1,000kg static load limit, fully assembled
Applicable Standards	Complies with ANSI/EIA-ECA-310-E; DIN41491:PART1.IEC297-2; DIN41494:PART7; GB/T3047.2-92 standard; compatible with ETSI standard
Suitable Applications	Used for mounting of 19" equipment such as patch panels, switches, UPS, AV and Security equipment

Images		
Image for Illustration purposes only	RoHS &	

Physical Properties		
Material	SPCC	
Colour	Black	
Static load limit	1,000kg	



GDR42U600X800FMD-240104.docx

Server Rack 42U



Supply Information	
SKU	Description
GDR42U600X800FMD	Floor Server 42RU 600Wx800Dx1995H mesh front, and rear mesh split lockable Doors Complete

For Compatibility information scan the QR code below or go to: https://www.garlandcables.com.au/data-racks-compatibility-chart/



- Madison reserves the right to make changes to the products described in this specification without prior notice.
- All values subject to factory tolerances

