Server Rack 42U



Data Racks / Floor Racks

| Description | 42U 800x1000 Floor Rack with mesh front, and rear mesh split lockable Doors. Removable and lockable side panels, top panel with ventilation holes and four cable entry points, bottom panel with two cable entry points. 4 Fan tray with thermostat, 3 fixed shelf, 8 way PDU with overload protection and switch, adjustable rails, levelling feet with heavy duty castors, grounding lugs, 40 x Nut/Bolt/washers, 1,000kg static load limit, vertical cable management, fully assembled |
|-----------------------|---|
| Applicable Standards | Complies with ANSI/EIA-ECA-310-E; DIN41491:PART1.IEC297-2; DIN41494:PART7; GB/T3047.2-92 standard; compatible with ETSI standard |
| Suitable Applications | Used for mounting of 19" equipment such as patch panels, switches, UPS, AV and Security equipment |

| Images | |
|--------------------------------------|--------|
| | |
| Image for Illustration purposes only | RoHS & |

| Physical Properties | | |
|---------------------|---------|--|
| Material | SPCC | |
| Colour | Black | |
| Static load limit | 1,000kg | |



GDR42U800X1000FMD-240104.docx

Server Rack 42U



| Supply Information | | |
|--------------------|--|--|
| SKU | Description | |
| GDR42U800X1000FMD | Floor Server 42RU 800Wx1000Dx1995H Front mesh, Rear split mesh, complete | |

For Compatibility information scan the QR code below or go to: https://www.garlandcables.com.au/data-racks-compatibility-chart/



- Madison reserves the right to make changes to the products described in this specification without prior notice.
- All values subject to factory tolerances

